



HAL
open science

H2: energy vector or source?

Isabelle Moretti

► **To cite this version:**

| Isabelle Moretti. H2: energy vector or source?. *L'Actualité Chimique*, 2019, 442. hal-02187452

HAL Id: hal-02187452

<https://univ-pau.hal.science/hal-02187452>

Submitted on 18 Jul 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

H₂: energy vector or source?

The di-hydrogen presents obvious advantages: as a fuel it can burn without emitting greenhouse gases or particles and as a means of storing electricity, it enables large scale and long period storage. In comparison with other methods of storage, gas storage mainly underground, allows for months of autonomy in a country such as France when all our batteries will be empty in few minutes and our dams in few days. For many analysts, hydrogen produced from renewable electricity is the missing element which could facilitate the integration of high levels of variable renewable energy into the energy system.

At the moment, H₂ is mainly used in industry as a raw material and is only starting to be used as a fuel for cars, trains and buses. It is also essentially manufactured from methane by CO₂ emitting processes. Alternatives exist such as electrolysis that splits water into hydrogen and oxygen. When the electricity is decarbonized, this H₂ is called green H₂. If the objective is the storage of the intermittent renewable electricity, fuel cells then allow to go back to electricity. Today these processes are not yet very efficient. Power to gas to power results in a 70% loss of energy, but improvements are expected, especially with the reversible Solid Oxide high temperature Fuel Cell (SOFC). Bacteria activity, algae and oxidation processes of for instance iron rich material are also potential sources of H₂ [1]. All these methods are not at the same stage of development (technology readiness levels TRL vary from 1 to 8) and do not result in a homogeneous H₂ price. Trying to predict which process will be the cheapest in a few years and thus predict "the" winner is what a lot of consultant and strategy departments are working on but this may not be the best approach. The most important trend in the new energy world is decentralization. Depending on the local constraints, the optimum role of H₂ in a green energy mix will differ and therefore the best technology will depend on the use for and the users. In addition, the transport of H₂ over large distances by boat is not easy; economically it is close to being a killing factor – the opposite of methane which can easily be liquefied. Liquefaction of H₂ consumes up to half of its energy.

Today industry is mainly focusing its efforts concerning green H₂ on reducing the price of electrolysis and fuel cells. This means that many companies are considering H₂ as a vector. However, two game changers are emerging which could be very disruptive.

First: native H₂

Natural H₂ produced by the water/rock interaction has been observed for long time but it was assumed that this production mainly occurred on a large scale along the mid oceanic ridges where hot oceanic newly created crust is in contact with sea water [2]. Roughly this reaction is an oxidation reaction of the Fe²⁺ (or Mg²⁺) and H₂ is released. The estimation of this production is between 4 000 and 10 000t/year/km of ridge.



New Caledonia: the hydrogen released from the subsurface reacts with the CO₂ in the atmosphere resulting in the carbonate precipitation. A natural carbon capture, utilization and storage (CCUS) process!

The conditions of deep water in the middle of nowhere with very hot fluids seem to exclude any economically viable production. However, for the past ten years, new data has shown that similar reactions happen at lower temperatures such as in Oman or New Caledonia [3] (*figure*) and that another oxidation reaction that takes place in old cratons where iron rich rocks are present also results in the continuous production of H₂ (in Russia [4], in the USA [5] and in Brazil [6]). At the same time, an accumulation of H₂ has been unexpectedly found in Mali at a shallow depth (110 m); the people who drilled the well were looking for water but the H₂ that they found instead has now been in production for five years [7]. It is burned to

produce electricity for the town. The pressure hasn't decreased during all these years strongly suggesting a continuous generation of H₂. This discovery also proved that carrier bed and seal exist for H₂ as for any other fluids in the subsurface. In 2018, the permanent monitoring of H₂ emanations carried out in Brazil by Engie has confirmed the continuous emission of H₂ in the studied area although the rate is not constant and varies during the day. The possibility of producing large and cheap quantities of H₂ from the subsurface is now a realistic hypothesis and various groups are working to better define the geological conditions that will allow long term production.

Second: H₂ produced using plasma torching

The second game changer comes simultaneously from the two main natural gas producers: the USA and Russia. H₂ could be produced using plasma torching of methane with black carbon as a by-product which, at least as a first step, could allow the process to be economically viable. The first large scale installation is currently managed in the States by monolith [8] and Gazprom announced by mid-2018 *via* a press release that they will massively invest in that technology in order to provide H₂ to western Europe in the coming decades with 100% H₂ in 2050... [9]. In Russia, as in the USA, because they will use up their huge reserves of cheap natural gas and their already in-place infrastructures, as soon as the plasma torch becomes cheaper, this H₂ is expected to rapidly reach a very competitive price. The current reserves of gas – 200 years of consumption worldwide – ensure the durability of such a green H₂ resource (from CH₄ but without producing CO₂). The technology used by Monolith is for a part tested in France, with Laurent Fulcheri's group at the Centre for Processes, Renewable Energies and Energy Systems at Mines ParisTech PSL Research University.

In another words, the probability of having access in the near future to a non-carbonated "natural" gas is not zero. In which case, the need to pass via electricity to decarbonize the energy mix will be questionable. It may even turn out to be the wrong solution, and consequently the need for huge batteries to store this electricity will also be questionable.

The future is not always predictable, even when we write it, and the race for cheap, green H₂ has started. Personally, I'm not sure that the electrolyzers will be the (only?) winner.

- [1] Oey M., Sawyer A.L., Ross I.L., Hankamer B., Challenges and opportunities for hydrogen production from microalgae, *Plant Biotechnol. J.*, **2016**, 14, p. 1487, doi: 10.1111/pbi.12516.
- [2] Charlou J.L., Donval J.P., Fouquet Y., Jean-Baptiste P., Holm N., Geochemistry of high H₂ and CH₄ vent fluids issuing from ultramafic rocks at the Rainbow hydrothermal field (36°14'N, MAR), *Chem. Geol.*, **2002**, 191, p. 345, doi: 10.1016/S0009-2541(02)00134-1.
- [3] Deville E., Prinzhofer A., The origin of N₂-H₂-CH₄-rich natural gas seepages in ophiolitic context: a major and noble gases study of fluid seepages in New Caledonia, *Chem. Geol.*, **2016**, 440, p. 139, doi: 10.1016/j.chemgeo.2016.06.011.
- [4] Larin N., Zgonnik V., Rodina S., Deville E., Prinzhofer A., Larin V.N., Natural molecular hydrogen seepage associated with surficial, rounded depressions on the European craton in Russia, *Nat. Resour. Res.*, **2014**, 24, p. 363, doi: 10.1007/s11053-014-9257-5.
- [5] Guélard J., Beaumont V., Rouchon V., Guyot F., Pillot D., Jézéquel D., Ader M., Newell K.D., Deville E., Natural H₂ in Kansas: deep or shallow origin?, *Geochem. Geophys. Geosyst.*, **2017**, 18, p. 1841, doi: 10.1002/2016GC006544.
- [6] Prinzhofer, A., Moretti I., Françolin J, Pacheco C., D'Agostino A., Werly J., Rupin F., Natural hydrogen continuous emission from sedimentary basins: the example of a Brazilian H₂-emitting structure, *Int. J. Hydrog. Energy*, **2019**, 44, p. 5675, doi: 10.1016/j.ijhydene.2019.01.119.
- [7] Prinzhofer A., Cissé C.S.T., Diallo A.B., Discovery of a large accumulation of natural hydrogen in Bourakebougou (Mali), *Int. J. Hydrog. Energy*, **2018**, 43, p. 19315, doi: 10.1016/j.ijhydene.2018.08.193.
- [8] <https://monolithmaterials.com/olive-creek>
- [9] www.bloomberg.com/news/articles/2018-11-08/russia-looks-to-hydrogen-as-way-to-make-gas-greener-for-europe

Dr Isabelle MORETTI,

E2S UPPA, formal Chief Scientific Officer & Top Expert at Engie, member of French Technology Academy.

*isabelle.moretti@engie.com