

Immobilization of a molecular Re complex on MOF-derived hierarchical porous carbon for CO2 electroreduction in water/ionic liquid electrolyte

Domenico Grammatico, Huan Ngoc Tran, Yun Li, Silvia Pugliese, Laurent Billon, Bao-Lian Su, Marc Fontecave

▶ To cite this version:

Domenico Grammatico, Huan Ngoc Tran, Yun Li, Silvia Pugliese, Laurent Billon, et al.. Immobilization of a molecular Re complex on MOF-derived hierarchical porous carbon for CO2 electroreduction in water/ionic liquid electrolyte. ChemSusChem, 2020, 13 (23), pp.6418-6425. 10.1002/cssc.202002014. hal-02950396

HAL Id: hal-02950396 https://univ-pau.hal.science/hal-02950396v1

Submitted on 13 Dec 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Immobilization of a molecular Re complex on MOF-derived hierarchical porous carbon for CO₂ electroreduction in water/ionic liquid electrolyte

5

7 Domenico Grammatico, ¹³ Huan Ngoc Tran, ² Yun Li, ² Silvia Pugliese, ¹² Laurent Billon, ³

Bao-Lian Su 1 * and Marc Fontecave 2 *

9

10

11

8

¹ Laboratory of Inorganic Materials Chemistry (CMI), University of Namur, 61 rue de Bruxelles, B- 5000 Namur, Belgium.

12

13

14

- ² Laboratoire de Chimie des Processus Biologiques, UMR CNRS 8229, Collège de France-
- 15 CNRS-Sorbonne Université, PSL Research University, 11 Place Marcelin Berthelot, 75005
- Paris, France.

17

³ Bio-inspired Materials Group: Functionality & Self-assembly, Universite de Pau et des Pays
 de l'Adour, E2S UPPA, CNRS, IPREM UMR 5254, 64000, PAU, France

2021

- * to whom correspondence should be addressed: marc.fontecave@college-de-france.fr;
- bao-lian.su@unamur.be

23

- 24 KEYWORDS: CO₂ electroreduction; catalysis; rhenium complex; heterogenization;
- 25 hierarchical porous carbon

26

27 Abstract

The development of molecular catalysts for CO_2 electroreduction within electrolyzers requests their immobilization on the electrodes. While a variety of methods have been explored for the heterogenization of homogeneous complexes, we here report a novel approach using a hierarchical porous carbon HPC material, derived from a Metal Organic Framework, as a support for the well-known molecular catalyst [Re(bpy)(CO) $_3$ Cl] (bpy = 2,2'-bipyridine). This cathodic hybrid material, named HPC@Re, has been tested for CO $_2$ electroreduction using a mixture of an ionic liquid (1-Ethyl-3-methylimidazolium tetrafluoroborate EMIM) and water as the electrolyte. The present study reveals that HPC@Re is a remarkable catalyst, enjoying excellent activity (high current densities and high turnover numbers) and good stability. Interestingly, it catalyzes the conversion of CO $_2$ into a mixture of carbon monoxide and formic acid, with a selectivity that depends on the applied potential. These results emphasize the advantages of integrating molecular catalysts onto such porous carbon materials for developing novel, stable and efficient, catalysts for CO $_2$ reduction.

Introduction

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

Carbon dioxide electroreduction into energy-dense carbon-based liquid or gaseous products is an attractive way to store renewable energies into chemical energy. However, because of the high stability of CO₂ and the requirement of multiple electron and proton-transfers for its transformation, catalysts are required to overcome the slow kinetics, minimize overpotentials and control product selectivity. While heterogeneous catalysts are generally favored due to their stability as well as facile product and catalyst recovery, homogeneous molecular metal complexes (coordination and organometallic complexes) have also been developed since the 1980's. In particular, they offer the unique opportunity to tune the coordination environment of the metal center and its reactivity via synthetic modifications of the ligands. The molecular strategy has been recently described in review articles.^[1,2] To reconcile these two approaches, homogeneous catalysts have sometimes been immobilized on heterogeneous conductive supports. However, this strategy has been applied to few molecular catalysts with limited success so far. [3-5] To illustrate the various techniques developed for providing access to modified electrodes, the case of the prototypical catalyst $[Re(bpy)(CO)_3C1]$ (bpy = 2,2'-bipyridine), highly selective for CO_2 to CO conversion, is interesting, since its immobilization has been studied using a variety of approaches. The first attempts to immobilize such complexes were achieved by Meyer and coworkers [6] and Abruña and coworkers [7] in 1985 and 1986, respectively, two years after the initial publication by Lehn reporting the catalytic activity of this complex for CO₂ reduction.^[8] In both cases, the catalyst was immobilized via electropolymerization of [Re(vbpy)(CO)₃Cl] (vbpy = 4-vinyl-4'-methyl-2,2'-bipyridine) on an electrode to afford catalytic poly-[Re(vpbpy)(CO)Cl] films, allowing electroreduction of CO₂ to CO with very high faradaic yields in CH₃CN. However, these films were shown to exhibit limited stability. A similar polymerization approach was recently developed by Kubiak and co-workers using 5-ethynyl-bipyridine derivatives, instead of vinylbipyridine, however, in that case very fast deactivation of the catalytic films was observed. [9] A different strategy for electropolymerization of a variant of Re(bpy)(CO)₃Cl was reported by Deronzier and co-workers.^[10] Upon electrochemical oxidation of a solution of $Re(pyrbpy)(CO)_3Cl$ (pyrbpy = 4-(4-Pyrrol-l-ylbuty1)4'-methyl-2,2'-bipyridine) using a Pt electrode, a polypyrrole-based film was deposited and found to catalyze the electroreduction in CH₃CN of CO₂ leading to CO as the only reduction product. However, the polymer was highly unstable and substantial loss of current was observed during electrolysis. In 1993, Kaneko and co-workers reported the immobilization, via simple adsorption, of Re(bpy)(CO)₃Br within a

Nafion[©] membrane, which is conductive and stable in various solvents and easily interfaces with electrode surfaces.^[11] The polymer-confined catalyst was active for CO₂ electroreduction in neutral aqueous electrolyte, leading to mixtures of CO, H₂ and formic acid, with a selectivity depending on the applied potential. Besides this immobilization involving polymers and membranes, covalent grafting to the electrode has also been explored. As o-quinone moieties found on the edge planes of graphite can condense with substituted o-phenylenediamines, Re(5,6-diamino-phenanthroline)(CO)₃Cl was used to modify graphite electrodes.^[12] The increased conjugation between the catalyst and the electrode was proposed to overcome poor conductivity issues in other polymeric films deposited onto electrodes. This system was very selective for CO formation (faradaic yield of 96%) in CH₃CN with high TONs. A conjugated polymer material incorporating Re(bpy)(CO)₃Cl motifs and covalently attached to a glassy carbon electrode was obtained by electropolymerization of a Re complex containing 2,2'-bipyridine-5,5'-bis-(diazonium) ligands. [13] These molecular films proved highly stable, allowing thousands of turnovers for


selective production of CO in CH₃CN.

Finally, non-covalent immobilization was achieved, exploiting π - π interactions between pyrolytic graphite and Re(pyrene-bpy)(CO)₃Cl, containing a pyrene-substituted bpy. This system was catalytically active for CO production but was rapidly deactivated, likely because of reduction of the pyrenyl moiety. The best result with such a non-covalent immobilization strategy was obtained by Kubiak and co-workers who developed a hybrid electrode resulting from the incorporation of Re(tBu-bpy)(CO)₃Cl, with tBu-bpy = 4,4'-di-*tert*-butyl-2,2'-bipyridine, into multi-walled carbon nanotubes (MWCNTs). This material proved stable and active in an aqueous electrolyte for highly selective CO production, at relatively low overpotential and with a current density of 4 mA.cm⁻². [15]

One of the drawbacks of all these immobilization strategies, with the exception of the MWCNT/Re(tBu-bpy)(CO)₃Cl system, resides in the need to introduce functionalities to the bipyridine ligand. This not only generates synthetic issues but also results in significant modifications of the electronic properties of the catalyst as well as of its reactivity. We thus thought of developing methods that allow the immobilization of the [Re(bpy)(CO)₃Cl] itself without synthetic modifications. Here we report the preparation and characterization of an original conductive carbon porous material and its utilization as a support for the [Re(bpy)(CO)₃Cl] catalyst, which can be easily fixed within the pores of the solid material. The novel hybrid material proved stable and active as a catalyst for CO₂ electroreduction, with high current

densities and high turnover numbers. Interestingly, this catalyst converts CO₂ into a mixture of CO and HCOOH, whose ratio depends on the applied potential.






Scheme 1: Synthesis of HPC and HPC@Re.


RESULTS AND DISCUSSION

Synthesis and characterization of the hierarchical porous ZIF8-derived carbon-HPC

The synthesis of hierarchical porous carbon (named HPC in the following) derived from the Metal Organic Framework ZIF8 was synthesized following a previous report, [16] however with significant modifications (Scheme 1). First, the ZIF8 precursor was infiltrated into the polystyrene spheres (PS) template and crystallized using a solution of CH₃OH/NH₃·H₂O. Second, a treatment at 450 °C under argon atmosphere, instead of washing with organic solvents used in the previous report, [16] was carried out in order to remove the PS template and thus obtain the hierarchical porous ZIF8 (HPZIF8). HPZIF8 shows slightly lower BET surface area (Figure S1 and Table S1) as compared to the previous report, [16] likely due to remaining PS beads in the sample. Scanning electronic microscope (SEM) and powder x-ray diffraction (XRD) characterizations of HPZIF8 show expected well-defined ZIF8 crystals (Figures S2-S3). HPZIF8 was finally pyrolyzed under inert atmosphere at 800 °C to obtain the final hierarchical porous carbon (HPC) material. HPC was characterized by various techniques. XRD pattern

confirmed that the material was not crystalline anymore (Figure S2). SEM images (Figure 1a) showed well-defined and well-distributed carbon particles with a three-dimensional tetrakaidecahedron morphology and with a uniform (monodisperse) diameter of 2 µm. This specific morphology is due to the use of PS latex as a template which controls the shape of the material. [16] The highly ordered porous carbon material showed a hexagonal-close-packed arrangement of PS nanospheres ??? (inset Figure 1a) with interconnected windows and porosity uniformly distributed. [17,18] N₂ physisorption analyses (Figure 1b and Figure S1) allowed to establish a BET surface area of 495 m².g⁻¹ and total pore volume of 1 cm³.g⁻¹ with around 25% of the total pore volume assigned, by the Horwart-Kawazoe method, to the micropores. The increase of the surface area due to the pyrolysis step leading to HPC (495 m².g⁻¹) from HPZIF8 (145 m².g⁻¹) is likely due to a complete removal of PS. N₂ adsorption isotherms are of typical type I, indicating the microporous character of the material with a pore size located at 0.5 nm. The presence of mesopores and macropores has been revealed by two N₂ adsorption uptakes at p/p₀ of 0.5 and 0.95-1.0, respectively, as shown in Figure 1b. The BJH analysis method gives a very sharp pic centered at 5 nm, corresponding to the hysteresis loop at p/p_0 of 0.5 [19] while the sharp N₂ adsorption uptake at p/p₀ of 0.95-1.0 is generated by the macropores of 380 nm observed by SEM (Figure 1a). The above analysis suggests HPC material contains a hierarchical macro-meso-microporous structure.





146

147

148

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

Figure 1: a) SEM image of HPC with enlargement (inset); **b)** N₂ adsorption-desorption isotherms of HPC and Re@HPC and pore size distribution (inset) made by BJH method of HPC.

149150

151

Functionalization of HPC material with a molecular complex

152 HPC was then used as a support for heterogeneizing the molecular [Re(bpy)(CO)₃Cl] complex, 153 named Re in the following. Re was immobilized without any further functionalization taking 154 advantage of the interconnected porosity of the support which improves the hosting properties. 155 The heterogenization of Re on HPC has been carried out as follows. First, Re was dissolved in 156 CH₂Cl₂ and the solution added dropwise to a sonicated dispersion of HPC in the same solvent 157 (Scheme 1). The solution was stirred for 1 hour and after centrifugation the supernatant 158 removed. Finally, the as-obtained hybrid system was dried overnight at room temperature. The relative amounts of starting precursors were chosen in order to obtain an initial weight Re:HPC 159 160 ratio of 1:9. Then, the obtained HPC@Re material was characterized not only to check for the 161 presence of the molecular complex within the solid but also to define morphology and structure 162 of the final material. 163 SEM images of Re@HPC showed that the morphology of the carbon particles was retained 164 (Figure S4). The presence of Re within the solid has been verified by Energy Dispersive X-Ray 165 mapping (EDX) (Figure S4) showing a uniform dispersion of the complex, as well as the 166 presence of residual Zn from ZIF8, even after pyrolysis. N₂ physisorption analysis after Re 167 loading showed a decrease of the BET surface area, indicating clearly the incorporation of the 168 molecular complex within the pores of the support (Figure 1b). The integrity of Re within the 169 solid material was proved by ¹H NMR spectroscopy after releasing the complex from Re@ 170 HPC by washing with CDCl₃. The spectrum of the solution proved identical to that of the pure 171 freshly prepared homogeneous complex (Figure S5). Finally, the amount of extractible complex 172 from 30 mg of HPC@Re using an organic solvent (CH₂Cl₂) was determined by UV-Visible 173 spectroscopy from the intensity of the absorption band at 387 nm, characteristic of the complex 174 (Figure S6). It was determined by ICP-MS that the sample contained 4.8 µmol of complex 175 leading to 0,16 µmol/mg of complex within Re@HPC.

176177

178

179

180

181

182

183

184

Preparation and characterization of the working HPC@Re/GDL electrode

An Re@HPC /GDL electrode (1cm²) was prepared by deposition of 5 mg HPC@Re on a commercial gas diffusion layer (GDL), as described in the experimental section. The total amount of Re in that electrode was determined by UV-Visible spectroscopy as described above for HPC@Re (Figure S6). The electrode was shown to contain 0.6 μmol.cm⁻². The CV of HPC@Re/GDL electrode in 0.1 M TBAPF₆ in CH₃CN at low scan rate of 10 mV.s⁻¹ (Figure S7) served to calculate the density of electroactive species from the charge integration of the peak at about -1.6 V vs Fc/Fc⁺, corresponding to the reoxidation of the complex.^[20] The data

led to a high surface density of 20 nmol.cm⁻², corresponding to approximately 3% of the total amount of complex present in the solid material. These numbers compare well with those determined for the best hybrid [Re(tBu-bpy)(CO)₃Cl]/MWCNT material (13 nmol.cm⁻², 1-8% of the total catalyst loaded) reported by Kubiak *et al.*^[15]

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

185

186

187

188

$Electrocatalytic \quad CO_2RR \quad in \quad water/1-Ethyl-3-methylimidazolium \quad tetrafluoroborate$

Since the electroreduction of CO₂ using the HPC@Re/GDL in water yielded mainly hydrogen

(EMIM) electrolyte

(data not shown), the reaction was studied in a CO₂-saturated solution of an ionic liquid in the presence of a small amount of water as a source of protons. Indeed, ionic liquids have been shown to facilitate CO2 electroreduction catalyzed by solid catalysts due to their ability to increase CO₂ solubility and activate CO₂. [21] A previous report showed that using an ionic liquid as both the solvent and electrolyte resulted in decreased overpotential and increased secondorder rate constant for CO₂ electroreduction to CO catalyzed by [Re(bpy)(CO)₃Cl]. [22] However, with such homogeneous systems, the viscosity of the medium results in strong limitations in mass transport (small diffusion coefficients) of the molecular catalyst and low current densities. This issue does not apply to an immobilized molecular complex. Thus, a mixture of an ionic liquid (1-Ethyl-3-methylimidazolium tetrafluoroborate) and water (named H₂O/EMIM in the following) has been chosen as the electrolyte for further CO₂ electroreduction studies using the HPC@Re/GDL electrode. The Linear Sweep Voltammograms (LSVs) of the HPC@Re/GDL electrode in 5% v/v H₂O/EMIM saturated with either Ar or CO₂ are presented in Figure 2a. A catalytic wave at an onset potential of -1.55 V vs Fc/Fc⁺ and developing further up to an applied potential of -2.05 V was observed only in the presence of CO₂ and was thus assigned to CO₂ reduction (Figure 2a). At potentials more negative than -2.1 V, a second wave was observed however also present for the HPC@Re/GDL electrode under argon, thus likely corresponding to proton reduction to H₂. Unfortunately, the evaluation of overpotential values is not trivial here as the equilibrium potentials of the CO₂/HCOOH and CO₂/CO couples in H₂O/EMIM are unknown. Controlled Potential Electrolysis (CPE) at different potentials between -1.75 V and -2.05 V versus Fc/Fc⁺ coupled with quantification of CO₂ reduction products has been carried out for 15 minutes in order to characterize the CO₂ reduction reaction. As expected the total current density increased with increased driving force up to 11 mA.cm⁻² at -2.05 V and was found to be stable during electrolysis at all potentials (Figure 2b). The high current densities translate

into remarkably high turnover numbers (TONs) and high Turnover Frequencies (TOFs). For example, at -2.05 V, 2026 TONs are reached after 15 min, which corresponds to a TOF value of 2.3 s⁻¹. As shown below, under these conditions, formate was the major product.

The only detected products in all experiments were H_2 and CO in the gaseous phase and formic acid in the liquid phase. Surprisingly, the selectivity of the reaction was found to be greatly dependent on the applied potential, with CO being the major product at the most anodic potentials and formic acid becoming the major product at potentials more cathodic than -1.9 V, while H_2 was a minor product at all potentials. This is clearly shown in Figure 2c which displays the Faradic yields (FY) of the various products at different potentials. At -1.75 V vs Fc/Fc⁺, FY(CO) and FY(H_2) were 79% (TON_{CO} 258 and TOF_{CO} 0.3 s⁻¹) and 9% respectively, and no formate could be found in the liquid phase. Screening the reaction at more negative potentials, CO formation decreased dramatically while FY(HCOOH) and FY(H_2), the latter to a smaller extent, increased. At -2.05 V, FY(CO), FY(H_2) and FY(HCOOH) were 3%, 20% and 76% (TON_{HCOOH} 1950 and TOF_{HCOOH} 2.2 s⁻¹) respectively (Figure 2c). Thus, the selectivity between CO vs HCOOH formation during electroreduction of CO₂ catalyzed by HPC@Re can be finely tuned by varying the applied potential.






Figure 2: Controlled potential electrolysis of CO₂ using the HPC@Re/GDL electrode: a) LSV in 5% v/v H₂O/EMIM saturated with CO₂ (black) or with Ar (red), scan rate 20 mV.s⁻¹; b) total current density at various applied potentials as a function of time; c) Faradaic Yields for CO, H₂ and formate after 15 min electrolysis at different potentials in 5% v/v H₂O/EMIM saturated with CO₂.

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

The observation of formate formation is unexpected since the Re complex is known to be a very selective catalyst for CO₂ electroreduction to CO in organic solvents. Interestingly, when, as a control experiment, CPE was carried out using the soluble Re complex in the same CO₂saturated 5% v/v H₂O/EMIM electrolyte, the reaction was shown to yield mainly H₂ with minor amounts of CO and almost no HCOOH, at all visited potentials (Figure S8). Furthermore, the current densities were much lower since at -1.85 V the current density reached a value of 0.3 mA.cm⁻² (Figure S8) for 12 μmol of Re catalyst (1 mM in 12 ml) as compared to 3 mA.cm⁻² for 0.6 µmol Re catalyst present in HPC@Re/GDL (Figure 2). This thus demonstrates the great impact of the solid support on the reaction outcome, both in terms of the activity and the selectivity. The effect on the activity is likely to be partly due to the hydrophobic nature of the environment provided by the pores in which the catalyst is bound, favouring CO₂ uptake and increasing CO₂ local concentration and to the absence of mass transport limitations which challenge the homogeneous catalyst. In contrast, the effect of the solid support on the selectivity is difficult to explain. Formation of formate cannot be explained by the catalytic properties of the support itself since, as a control experiment, CPE of CO₂ using an HPC/GDL electrode, not loaded with the Re complex, under identical conditions, gave very different results (Figure S9). For example, at -1.85 V, with a current density of 1 mA.cm⁻², no formate could be detected, as compared to 3 mA.cm⁻² and a FY(HCOOH) of 20% for the HPC@Re/GDL electrode, and at -1.95 V, with a current density of 2 mA.cm⁻², a FY(HCOOH) of 15% was obtained, as compared to 6 mA.cm⁻² and a FY(HCOOH) of 50% for the HPC@Re/GDL electrode. There is, to our knowledge, one study reporting formate production during electroreduction of CO₂ catalyzed by the Re complex, with a HCOOH/CO selectivity depending on the applied potential as well.^[11] Interestingly, in that case, the catalyst was incorporated into a Nafion membrane and electrolysis was carried out in a phosphate aqueous electrolyte, explaining why the major product at almost all potentials applied was H₂. The activity, in terms of current density, of that system was furthermore much lower than that reported here. While formate production using the HPC@Re catalyst is likely to proceed via a Re-H hydride species reacting with CO₂, [23,24] in contrast to CO production

which derives from a Re-CO₂ intermediate, it is so far unclear why the HPC support favours

such a mechanism at very cathodic potentials and how the support tunes the HCOOH/CO selectivity. These mechanistic aspects deserve further investigation.

Finally, long-term CPE was carried out for 2 hours at -1.75 V (formation of CO and H₂) and -1.95 V (formation of CO, HCOOH, H₂) *vs* Fc/Fc⁺ (Figure 3). The system proved very stable during electrolysis in terms of both current density and selectivity. After 2 hours at -1.75 V, 3155 TON_{CO} were achieved corresponding to a TOF_{CO} of 0.4 s⁻¹. Furthermore, post-electrolysis characterization of the electrode by SEM showed that the porosity of the system was retained even if slight agglomeration of the particles was observed (Figure S10). Finally, the amount of Re released in solution after 2 hours electrolysis was measured by ICP-MS and found to be within 5 to 10%, from one experiment to another, with respect to the initial amount of Re initially present on the electrode. Based on the results given above (Figure S8), this amount is far too small to account for the CO₂ reduction activity of the electrode.




Figure 3: Long-term electrolysis: current density and FY as a function of time during CPE at -1.75 V vs Fc/Fc⁺(\mathbf{a}) and at -1.95 V vs Fc/Fc⁺(\mathbf{b}) under CO₂ in 5% v/v H₂O/EMIM using the HPC@Re/GDL. Faradaic yields for CO (red dots), H₂ (black squares) and formate (blue diamonds).

Conclusion

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

We have developed a novel hybrid solid catalyst, HPC@Re, for CO₂ electroreduction to CO and HCOOH. Thanks to the hierarchical porosity of the porous and conductive carbon material HPC, large amounts of the molecular catalyst [Re(bpy)(CO)₃Cl] can be easily immobilized without any functionalization. We anticipate that HPC can be further used for heterogeneization of other complexes. In order to optimize catalysis, CO₂ electroreduction has been studied in an ionic liquid electrolyte in the presence of water, known to favour CO₂ solubility and activation. To the best of our knowledge, this is the first example of a heterogenized molecular complex characterized for CO₂ reduction catalysis in an ionic liquid. HPC@Re/GDL electrodes thus provide high current densities (up to 11 mA.cm⁻²), high TOF_{CO+HCOOH} (2.3 s⁻¹) and display good stability. When compared to other hybrid solid electrodes in which [Re(bpy)(CO)₃Cl] has been immobilized, [6-15] the HPC@Re/GDL electrode is among the most efficient and stable ones. In addition, this novel electrode is unique in providing not only CO but also HCOOH as CO₂ reduction products, with FY(H₂) not exceeding 20%, in marked contrast with the other comparable systems which are selective for CO production and in contrast with the homogeneous catalyst which favours proton reduction over CO₂ reduction and is quite inefficient in the same water/ionic liquid system. The CO/HCOOH ratio can be tuned with the applied potential since it decreased as the potential is shifted to more cathodic values. The combination of a water/ionic liquid electrolyte system, the hierarchical porosity of the support facilitating mass exchange and transfer, [25] and the hydrophobic environment provided by the pores in which the molecular complex is fixed is likely to explain the remarkable and unique performances of HPC@Re as a CO2 reduction catalyst. However, further studies are required to understand how the support drives and controls the reactivity of the immobilized complex.

Experimental section

General methods

317

318

337

344

319 All chemicals were received from commercial sources and used as received. Zinc nitrate 320 hexahydrate (Zn(NO₃)·6H₂O, 99%), 2-methyilimidazole (98%), tetrabutylammonium hexafluorophosphate (TBAPF₆, 98%), Nafion[©] perfluorinated resin (10 µL of a 5 wt% solution 321 322 in mixture of lower aliphatic alcohols containing 5% water), absolute ethanol (CH₃CH₂OH), 323 methanol (CH₃OH, 99%), dichloromethane (CH₂Cl₂, 99 %), acetonitrile (CH₃CN, 99.8%), 324 chloroform-d (CDCl₃, 99.8%) and ammonia solution (NH₃·H₂O, 32%) were purchased from 325 Sigma-Aldrich. 1-Ethyl-3-methylimidazolium tetrafluoroborate (>98%) was purchased from 326 IOLITEC Ionic liquid technologies GmbH. [Re(bpy)(CO)₃Cl] was synthesized as previously 327 reported by Kubiak et al. [26] 328 UV-vis spectra were recorded using a Cary 100 UV-vis spectrophotometer (Agilent). ¹H 329 spectra were recorded on a Bruker Avance-III 300 NMR spectrometer (300 MHz) at room 330 temperature. The Rhenium concentrations in the electrolyte were assessed using an Agilent 331 7900 quadrupole ICP-MS. Liquid samples were sprayed through a micro-nebulizer in a Scott 332 spray chamber prior to ionization. An indium internal standard was injected after inline mixing 333 with the samples to correct for signal drift. Calibration solutions with Re concentrations 334 encompassing the full range of sample concentrations were used to convert measured counts to 335 concentrations. Reported uncertainties were calculated using algebraic propagation of blank 336 substraction and sample count standard deviations (n=3).

Material characterization

- 338 Scanning electron microscope (SEM) images were performed by using a JEOL 7500F
- microscope operating at 15kV with EDX detector incorporated and a Hitachi S-4800 operating
- at 5kV. X-ray diffraction (XRD) characterization was carried out by Panalytical X'Pert PRO
- diffractometer (Cu K α radiation, Bragg-Brentano geometry, sealed tube operated at 45 mA 30
- 342 kV X'Celerator linear detector). Nitrogen physisorption analyses were performed with ASAP
- 343 2420 using a platinum resistance device and liquid nitrogen as adsorbed molecule.

Synthesis of HPZIF8

- Polystyrene spheres (PS) (the size of 400 nm) were synthesized as previously reported^[16] and
- used as a template for the preparation of a hierarchical porous ZIF8 (HPZIF8). HPZIF8 with
- polystyrene (HPZIF8@PS) was also prepared using a protocol from Chen et al. [16], via
- 348 infiltration of the ZIF8 precursor into the PS spheres template. The following steps were
- 349 modified from the previous protocol to obtain the HPZIF8. This, was prepared from

- 350 HPZIF8@PS treating it at 450 °C during 4 hours under Argon atmosphere for removing the PS
- 351 beads.
- 352 Synthesis of HPC
- 353 The hierarchical porous carbon (HPC) derived from ZIF8 was obtained by heating the HPZIF8
- at 800 °C during 3 hours under Argon atmosphere. The HPC was used without further
- 355 treatment.
- 356 **Preparation of HPC@Re**
- 357 The preparation of Re complex loading on HPC material was carried out as follows: the solution
- of [Re(bpy)(CO)₃Cl] (6 mg) in CH₂Cl₂ (10 mL) was added dropwise to a sonicated dispersion
- of HPC (50 mg) in CH₂Cl₂ (20 mL). The suspension was then centrifuged for removing the
- 360 supernatant. The obtained material was then dried overnight under vacuum condition at room
- temperature and used without further treatments.
- 362 These materials were characterized by: N₂ physisorption analyses, SEM images, EDX mapping
- and XRD (Supporting Information).
- The amount of Re complex loaded was quantified by UV-Visible spectroscopy (Figure S6):
- after extraction of 30 mg of HPC@Re with 20 mL of CH₂Cl₂ the solution was analysed for its
- absorption at 387 nm, characteristic of [Re(bpy)(CO)₃Cl] and the latter was compared to
- calibration curve prepared with pure [Re(bpy)(CO)₃Cl]. HPC@Re was also treated with CDCl₃
- for extraction of the complex and characterization by ¹H NMR (Figure S5), in order to confirm
- 369 the integrity of the complex.
- 370 Electrode preparation
- 371 HPC@Re (5 mg) was sonicated 1 hour in absolute ethanol (200 µL) and a solution of Nafion
- perfluorinated resin (10 µL of a 5 wt% solution in mixture of lower aliphatic alcohols containing
- 373 5% water). The suspension was then, carefully, deposited by drop casting on a gas-diffusion
- Layer, GDL (AVCarb GDS 3250; 1 cm²) in order to have a uniform deposition. The electrode
- was then dried in air overnight at room temperature. For all the experiments the working
- electrodes were prepared in the same way.
- 377 Electrode characterization
- 378 SEM images of the HPC@Re/GDL electrode were obtained before and after 2 hours
- 379 electrolysis. The amount of Re complex present on the GDL was quantified by UV-Visible
- 380 spectroscopy as described above via extraction of the complex from the HPC@Re/GDL
- electrode immersed in 20 mL of CH₂Cl₂ (Figure S6) and quantification by comparison with the
- 382 calibration curve.

Electrochemical characterization

383

384

385

386

387

388

389

390

391

392

All electrochemical characterization and electrolysis experiments were carried out using a Biologic SP300 potentiostat with two-compartment cell with an Ag/AgCl/3M KCl reference electrode, placed in the same compartment as the working HPC@Re/GDL electrode. A platinum counter electrode was placed in a separate compartment. The two compartments were separated by a membrane (Fumasep FBM-Bipolar Membrane). The electrolyte was CO₂saturated 5% v/v H₂O/EMIM (12.5 mL). The electrochemical cell was first purged with CO₂ at a flow rate of 20 mL.min⁻¹ for 1 h prior to catalytic tests using a mass flow controller (Bronkhorst EL-FLOW model F-201CV). All potential values are given versus the potential of the Fc/Fc⁺ couple added as an internal standard to the solution after measurement. In 5% v/v $H_2O/EMIM: E1/2(Fc/Fc^+) = 0.35V \text{ vs Ag/AgCl (Figure S11)}$

- 393
- 394 CVs for the determination of surface density of electrochemically active sites were recorded in
- 395 CH₃CN, 0.1 M TBAPF₆ with a scan rate of 10 mV.s⁻¹.
- The surface loading ($\Gamma[Re]$ as mol.cm⁻²) of the catalyst was calculated through the integration 396
- 397 of the reoxidation wave in the CV scan (Figure S7) using the equation:

$$\Gamma[Re] = \frac{q}{nFA}$$

- 399 where q is the charge (C) obtained from integration of the oxidation wave, n the number of
- 400 electrons in the redox process per Re center (n = 1), F is the Faraday constant (96485 C.mol⁻¹),
- and A is the geometrical electrode area (1 cm²).^[27] 401
- 402 The homogeneous electrochemical experiments were carried out under the same conditions
- 403 described above using the same electrochemical cell. A glassy carbon electrode (1 cm²) was
- 404 used as working electrode in a solution 1 mM of [Re(bpy)(CO)₃Cl] in 5% v/v H₂O/EMIM.
- 405 H₂ and CO were identified and quantified using a gas chromatograph (SRI 8610C) equipped
- with a packed Molecular Sieve 5 Å column for permanent gases separation and a packed 406
- 407 Haysep-D column for light hydrocarbons separation. Argon (Linde 5.0) was used as carrier gas.
- 408 A flame ionization detector (FID) coupled to a methanizer was used to quantify CO while a
- 409 thermal conductivity detector (TCD) was used to quantify H₂. The liquid-phase products were
- 410 quantified using an ionic exchange chromatography system (883 Basic IC plus; Metrohm).

413	Acknowledgements
1	· · · · · · · · · · · · · · · · · · ·
414	The PhDs of D.G and S.P are financially supported from the European School on Artificial
415	Leaf: Electrodes & Devices (eSCALED) project. This work is part of the eSCALED project
416	which has received funding from the European's Union's Horizon 2020 research and
417	innovation programme under the Marie Sklodowska-Curie grant agreement No 765376.
418	This research used resources of the Electron Microscopy Service located at the University of
419	Namur. This Service is member of the "Plateforme Technologique Morphologie –Imagerie".
420	SEM images were also collected by F. Pillier at the Laboratoire Interfaces et Systèmes
421	Electrochimiques.
422	Parts of this work were supported by IPGP multidisciplinary program PARI, and by Paris–IdF
423	region SESAME Grant no. 12015908.
424	
425	

427 References

- 428 [1] R. Francke, B. Schille, M. Roemelt, *Chem. Rev.* **2018**, *118*, 4631–4701.
- 429 [2] H. Takeda, C. Cometto, O. Ishitani, M. Robert, ACS Catal. 2017, 7, 70–88.
- 430 [3] N. Elgrishi, M. B. Chambers, X. Wang, M. Fontecave, *Chem. Soc. Rev.* **2017**, *46*, 761–431 796.
- 432 [4] C. Sun, R. Gobetto, C. Nervi, New J. Chem. 2016, 40, 5656–5661.
- 433 [5] L. Sun, V. Reddu, A. C. Fisher, X. Wang, *Energy Environ. Sci.* **2020**, *13*, 374–403.
- 434 [6] T. R. O'Toole, L. D. Margerum, T. D. Westmoreland, W. J. Vining, R. W. Murray, T. J. Meyer, *J. Chem. Soc. (,) Chem. Commun.* **1985**, 1416–1417.
- 436 [7] C. R. Cabrera, H. D. Abruña, *J. Electroanal. Chem. Interfacial Electrochem.* **1986**, 209, 101–107.
- 438 [8] J. Hawecker, J.-M. Lehn, R. Ziessel, J. Chem. Soc. (,) Chem. Commun. 1983, 536–538.
- 439 [9] A. Zhanaidarova, A. L. Ostericher, C. J. Miller, S. C. Jones, C. P. Kubiak, 440 *Organometallics* **2019**, *38*, 1204–1207.
- 441 [10] S. Cosnier, A. Deronzier, J.-C. Moutet, *J. Electroanal. Chem. Interfacial Electrochem.* 442 **1986**, 207, 315–321.
- 443 [11] T. Yoshida, K. Tsutsumida, S. Teratani, K. Yasufuku, M. Kaneko, *J. Chem. Soc. {*, *}* 444 *Chem. Commun.* **1993**, 631–633.
- 445 [12] S. Oh, J. R. Gallagher, J. T. Miller, Y. Surendranath, *J. Am. Chem. Soc.* **2016**, *138*, 1820–446 1823.
- 447 [13] J. Willkomm, E. Bertin, M. Atwa, J.-B. Lin, V. Birss, W. E. Piers, *ACS Appl. Energy*448 *Mater.* **2019**, 2, 2414–2418.
- 449 [14] J. D. Blakemore, A. Gupta, J. J. Warren, B. S. Brunschwig, H. B. Gray, *J. Am. Chem.* 450 *Soc.* **2013**, *135*, 18288–18291.
- 451 [15] A. Zhanaidarova, S. C. Jones, E. Despagnet-Ayoub, B. R. Pimentel, C. P. Kubiak, *J. Am. Chem. Soc.* **2019**, *141*, 17270–17277.
- 453 [16] K. Shen, L. Zhang, X. Chen, L. Liu, D. Zhang, Y. Han, J. Chen, J. Long, R. Luque, Y. Li, B. Chen, *Science* **2018**, *359*, 206–210.
- 455 [17] M. Wu, Y. Li, Z. Deng, B. L. Su, *ChemSusChem* **2011**, *4*, 1481–1488.
- 456 [18] S. Suter, S. Haussener, *Energy Environ. Sci.* **2019**, *12*, 1668–1678.
- 457 [19] J.-P. Song, L. Wu, W.-D. Dong, C.-F. Li, L.-H. Chen, X. Dai, C. Li, H. Chen, W. Zou, 458 W.-B. Yu, Z.-Y. Hu, J. Liu, H.-E. Wang, Y. Li, B.-L. Su, *Nanoscale* **2019**, *11*, 6970–6981.
- 460 [20] M. L. Clark, P. L. Cheung, M. Lessio, E. A. Carter, C. P. Kubiak, *ACS Catal.* **2018**, 8, 2021–2029.
- 462 [21] B. A. Rosen, A. Salehi-Khojin, M. R. Thorson, W. Zhu, D. T. Whipple, P. J. A. Kenis,
 463 R. I. Masel, *Science* 2011, *334*, 643–644.
- 464 [22] D. C. Grills, Y. Matsubara, Y. Kuwahara, S. R. Golisz, D. A. Kurtz, B. A. Mello, *J. Phys. Chem. Lett.* **2014**, *5*, 2033–2038.
- 466 [23] J. Agarwal, R. P. Johnson, G. Li, J. Phys. Chem. A 2011, 115, 2877–2881.
- 467 [24] A. J. Morris, G. J. Meyer, E. Fujita, Acc. Chem. Res. **2009**, 42, 1983–1994.
- 468 [25] X. Zheng, G. Shen, C. Wang, Y. Li, D. Dunphy, T. Hasan, C. J. Brinker, B. L. Su, Nat.

Commun. 2017, 8, 1–9.
J. M. Smieja, C. P. Kubiak, Inorg. Chem. 2010, 49, 9283–9289.
B. Reuillard, K. H. Ly, T. E. Rosser, M. F. Kuehnel, I. Zebger, E. Reisner, J. Am. Chem. Soc. 2017, 139, 14425–14435.