



HAL
open science

Characterization of Biogas and Biomethane: Trapping, Analysis and Speciation of Trace Compounds

Aurore Lecharlier, Carrier Hervé, Guilhem Caumette, Isabelle Le Hécho

► **To cite this version:**

Aurore Lecharlier, Carrier Hervé, Guilhem Caumette, Isabelle Le Hécho. Characterization of Biogas and Biomethane: Trapping, Analysis and Speciation of Trace Compounds. 9th GERG Young Researchers' Awards, EGATEC 2019, 6 – 8 November, Groningen, The Netherlands, Nov 2019, Groningen, Netherlands. hal-03339125

HAL Id: hal-03339125

<https://univ-pau.hal.science/hal-03339125>

Submitted on 9 Sep 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Characterization of Biogas and Biomethane: Trapping, Analysis and Speciation of Trace Compounds

Lecharlier A.^{a,b}, Carrier H.^b, Caumette G.^c, Le Hécho I.^a

^a CNRS/Univ Pau & Pays Adour/E2S UPPA, IPREM, UMR5254, Helioparc-2 Avenue du Président Angot, 64000 Pau, France

^b CNRS/Total/Univ Pau & Pays Adour/ E2S UPPA, LFCR-IPRA UMR 5150, 64000 Pau, France


^c Teréga, 40 Avenue de l'Europe CS 20 522-64010 PAU Cedex, France

9th GERG Young Researchers' Awards, EGATEC 2019, 6 – 8 November, Groningen, The Netherlands

Some numbers

BIOMETHANE (1,2)	NATURAL GAS (3)
≥ 97% CH ₄	70-90 % CH ₄
30-35 MJ/Sm ³	37.5-40.5 MJ/Sm ³
GHG emission saving when producing and combusting biomethane compared to NG: 218 kg CO₂-eq/MWh (4,5)	
World production in 2016 (billion Sm³)	
BIOGAS (6)	NATURAL GAS (7)
61	3551.6

Biogas production in 2016 (6)



European Union (1,8,9,10)

- > 17400 biogas production plants
- > 400 biogas upgrading plants (biomethane)
- > 1.5 million Sm³ biomethane injected in NG grid
- > 160 million Sm³ biomethane for transport fuel

Methods

Target compounds	Pre-concentration	Quantification and Speciation
(H)VOC oxygenated N-, S-, Si-	Adsorption	TD-GC-MS
Metals	<ul style="list-style-type: none"> Cryotrapping Bubbling <ul style="list-style-type: none"> 10%_w HNO₃ / 5%_w H₂O₂ for metal(loid)s 1%_w KMnO₄ / 5%_w H₂SO₄ for Hg Chemotrapping 	<ul style="list-style-type: none"> GC-ICP-MS ICP-MS GC-ICP-MS / AFS


Biogas & biomethane sampling sites:

- Landfills
- Agricultural waste digesters
- Household waste digesters
- Food waste digesters
- ...
- a.m.a.p. different sites !

References:

- Cucchiella F. et al. Energy Conversion and Management 119 (2016) 338–351
- Rauch J. et al. 2018. J. Phys.: Conf. Ser. 1065 202007
- OECD, IEA, Eurostat, 2004. Energy Statistics Manual
- AFG, 2018. Gaz renouvelables: les leviers du développement
- GRDF, GRTgaz, SPEGNN, SER, Teréga. Panorama du gaz renouvelable en 2017
- World Bioenergy Association. Global Bioenergy Statistics 2018 Report
- BP Statistical Review of World Energy, June 2017, 66th edition
- Scarlat N. et al. Renew Energy. 2018 Dec;129:457–72
- Arrhenius K. et al. Biomass Bioenergy. 2017 Oct;105:127–35
- Blaisonneau L. et al. ENEA Consulting; 2017

Context



Contact: aureore.lecharlier@univ-pau.fr

SECTOR INTEGRATION:

Biomethane must meet the same norms and specifications as NG to be injected in the gas grid

BUT

KNOWLEDGE GAP on trace compounds

- S-, N-, Si-
- (H) VOC
- Oxygenated organic compounds
- Metal(oid) compounds

Impacts ??

- on gas infrastructures
- on environment
- on users

HENCE

Need to expand knowledge on biomethane's trace compounds

Objectives

1

On site **pre-concentration** of biomethane's trace compounds:

- high pressure
- adsorption** bubbling, cryotrapping, chemotrapping

2

Quantification and speciation




LAB SCALE OPTIMIZATION:

- Chemically = targeted adsorption
- Physically = under pressure (≤ 100 bar)

Materials and methods: DEVELOPMENT

- Criteria** for pertinent **adsorbent choice**:
 - Quantitative adsorption and desorption
 - Polarity, strength
 - Compatibility thermal desorption
 - Cover all range target analytes (broad volatility range)
- Mutlibeds** self-assembly from A to Z
 - ⚠ T compatibility




OPTIMIZATION & VALIDATION

- Standard** gases (target analytes in CH₄)
 - Pure single gases
 - Mix of standard gases
- Real** biogas and biomethane (in Tedlar bag or ogive)

- at P_{atm}
- at P_{grid} (40 - 100 bar)


- Blanks
- Calibrations
- ...



FIELD IMPLEMENTATION: lab work and knowledge integrated in a field case

on site **sampling and pre-concentration** of trace compounds in

- Natural gas
- Biomethane
- Biogas



- polyvalent
- easy handling
- no sample transfer
- anywhere at any pressure (≤ 100 bar)
- ATEX

DELIVERABLES

- Optimized polyvalent **field tool** for gaseous trace compounds pre-concentration
- Database** biomethane's trace compounds i.f.o. feedstock & operating conditions
- Adapt **upgrading** technologies
- Adapt existing / define new **norms** and **specifications** for biomethane grid injection