



HAL
open science

Optimizing Chaotic Mixing in Open Ponds with Lateral Mixers for Enhanced Spirulina Cultivation.

Imane Skifa, Nicolas Chauchat, Pierre-Henri Cocquet, Yves Le Guer

► To cite this version:

Imane Skifa, Nicolas Chauchat, Pierre-Henri Cocquet, Yves Le Guer. Optimizing Chaotic Mixing in Open Ponds with Lateral Mixers for Enhanced Spirulina Cultivation.. AlgaEurope 2023, Dec 2023, Prague (Czech Republic), Czech Republic. hal-04473655


HAL Id: hal-04473655

<https://univ-pau.hal.science/hal-04473655>

Submitted on 22 Feb 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Optimizing Chaotic Mixing in Open Ponds with Lateral Mixers for Enhanced Spirulina Cultivation

Imane SKIFA*,


Nicolas CHAUCHAT, Pierre-Henri COCQUET, Yves LE GUER

SIAME/Université de Pau et Pays de l'Adour - E2S UPPA - IPRA - 64000 Pau, France.

*imane.skifa@univ-pau.fr




1. Spirulina cultivation



- The dominant fluid stirring mechanism in open ponds is **paddlewheel**.

- Spirulina is mainly cultivated in **open ponds (83%)** rather than photobioreactors [1].

2. Methodology



Simulation Set-up	
STATE	Transient
FLOW REGIME	Laminar
BOUNDARY CONDITIONS	Periodic 1 inlet 1 outlet
FLUID	Water based liquid
INLET VELOCITY	0.01 m/s
DYNAMIC VISCOSITY (μ)	3×10^{-3} Pa.s
REYNOLDS NUMBER	331


- We seek to optimize the mixing process within **rectangular ponds**, which can be visualized as **2D plane media**.
- Strategically positioned jets along the lateral sides of the pond will generate fluid circulation.

Objective


The current production rates in ponds are limited at approximately **1-2 g/L** of dry matter, indicating a relatively **low output**.

Our objective is to ascertain optimal mixing protocols by combining suitable solutions with varying jet positions, which will ensure better nutrients and CO₂ distribution.

3. Results



- Proposing a **dual-system strategy** with a single inlet and outlet, our goal is to combine two distinct solutions.
- The methodology entails alternating between these solutions over a **designated timeframe**.



4. Conclusions & perspectives

- Configuration with **lateral mixers** in open ponds remain largely unexplored.
- To optimize the mixing process within rectangular ponds, we define a new mixing protocols by combining different solutions to achieve a **homogeneous mixing**.
- The physical mechanism of **chaotic mixing** will be employed. This involves introducing temporal modulations of velocities in the 2D plane flow, resulting in a gentle yet highly effective mixing action by stretching and folding the fluid filaments.
- After mixing patterns optimization, we will validate our protocols by experimenting with **spirulina** cultivation.

References

[1] R. Araújo, F. Vázquez Calderón, J. Sánchez López, I.C. Azevedo, et al., (2021). Current Status of the Algae Production Industry in Europe: An Emerging Sector of the Blue Bioeconomy, *Front. Mar. Sci.* 7:626389